



## Soft Sided Handheld Terminal Heater

1650 Dove Court Marietta, Georgia 30064 Phone: 770.499.9420 Fax: 770.499.9423 [www.jlcsolutions.biz](http://www.jlcsolutions.biz)



***JLC Solutions*** is proud to announce an exciting advance in heaters for portable handheld terminals. This heater will allow you to make full use of the handheld terminal in any and all environments. Our new soft-sided terminal heater is designed to work most handheld terminals.

The new JLC heater is made from durable ballistic nylon for years of use and incorporates the thermostatically controlled heating elements that JLC has used successfully for more than 10 years. The lightweight heater is powered by a lithium ion battery and is designed to be worn with the included shoulder strap.

The JLC heater will keep the terminal warm and dry, and the padded case will help protect your investment. Very importantly, this heater will significantly extend the terminal's battery life even in sub-zero environments. Condensation on the scanner lens and the display screen will be virtually eliminated.

In the harshest environments where rapid or extreme temperature changes occur, such as traveling from a refrigerated or frozen storage area to a loading dock, from an air-conditioned warehouse to outdoors, for everyday outdoor use or any place where condensation is likely to occur, this heater will enable your portable terminal to function to your expectations.

**Soft Sided Handheld Terminal Heater**
**Product Specifications**

Part Number	Description
751	One (1) Soft Sided Heater Two (2) Lithium Ion Batteries One (1) two bay battery charger One (1) shoulder strap
752	Two (2) Soft Sided Heaters Four (4) Lithium Ion Batteries One (1) two bay battery charger Two (2) shoulder straps

**Heater**
**Mechanical Dimensions**

Interior	4.5" x 3.7" x 9.25" 114mm x 94mm x 241mm
Exterior	4.7" x 4.0" x 9.5" 120mm x 101mm x 241mm

**Electrical**
**RoHS Compliant**
**Thermal Heat Protection at 152 degrees C**
**LED Indicators**

Green: Power On  
Orange: Heater On

**Ballistic Nylon (padded)**
**Battery Charger**
**Mechanical**

Two bay charger; charges two batteries independently and simultaneously

**Electrical**
**Power Input Requirements:**

AC Input 100 – 240 Volts  
2.0 Amps  
50 – 60 Hz  
56 Watts Max

**LED Status**

Solid Red: Charging  
Solid Green: Fully Charged  
Blinking Red: Fault Warning

**Certification**

Complies with part 15 of the FCC rules

**Battery**

Lithium Ion

**Weight**

Battery: 13.75 ounces  
Heater Pouch with strap: 18.5 ounces

**Warranty**
**Standard**

The factory warranty is one (1) year limited parts and labor.

Specifications subject to change without notice